# NoSQL Big Data Systems

Dr. Rubi Boim

#### NoSQL


- Non SQL
- Not Only SQL
- Non schema SQL
- Non Relational SQL

Most (distributed) Big Data storage / database systems

SQL is an API

#### NoSQL - motivation

- Scaling issues of RDBMS
- Variety of data (schema-less)
- Read / write performance



Product needs of Google / Amazon / Facebook...

### NoSQL - popular properties

- "Simpler" design / API
- Availability over Consistency
- Performance over ACID transactions extremely fast read/write at scale
- Distributed scale wide (commodity hardware)
- Schema less
- Multi data center

# NoSQL - main types


- Key Value
- Document
- Graph
- Wide column

by their internal data model / API

## NoSQL - Key Value

- "Simplest" NoSQL database
- Hash table / dictionary key-value pairs
- CRUD API

```
create(key/value)
read(key)
update(key/value)
delete(key)
```




## NoSQL - Key Value

- "Simplest" NoSQL database
- Hash table / dictionary key-value pairs
- CRUD API


```
create(key/value)
read(key)
update(key/value)
delete(key)
```

popular systems dynamo, levelDB, redis, memcached



#### NoSQL - Document

- Scheme less "document" accessible by unique key
- Document encoding json / xml / yaml / bson
- Stores all information of a given object in a single place
- CRUD API but not only (find, sort...)



#### NoSQL - Document


- Scheme less "document" accessible by unique key
- Document encoding json / xml / yaml / bson
- Stores all information of a given object in a single place
- CRUD API but not only (find, sort...)

popular systems mongoDB, CouchDB

```
value
 key
"123"
       "fname": "Lebron",
        "Iname": "James",
        "teams":
         ["Cleveland", "Miami", "LA"],
```


## NoSQL - Graph

- Based on graph theory nodes, edges, properties, weights
- ACID / Transactions not always
- Built in graph algorithms



## NoSQL - Graph


- Based on graph theory nodes, edges, properties, weights
- ACID / Transactions not always
- Built in graph algorithms



popular systems neo4j, DataStax enterprise graph

#### NoSQL - Wide column

- Tables, rows, columns can vary from row to row within a table
- Can be viewed as 2-dimensional key-value store
- Custom API
   with some SQL sometimes (CQL)
- NOT a columnar database but can be sometimes




#### NoSQL - Wide column

- Tables, rows, columns can vary from row to row within a table
- Can be viewed as 2-dimensional key-value store
- Custom API
   with some SQL sometimes (CQL)
- NOT a columnar database


but can be sometimes

popular systems
Cassandra, BigTable,
DynamoDB, HBase



#### NoSQL - Wide column

- A lot more on these systems
- Stay tuned:)




Basically Available
Soft state
Eventual consistency

# ACID (reminder)

- Atomicity
- Consistency correctness / referential integrity (foreign key) - NOT like in CAP
- Isolation
- Durability

#### BASE

- Basically Available
   There will be a response even if node fails (response=fail)
- Soft state
   State can change even if no read/write are performed (the system is aiming towards consistent)
- Eventual consistency reads may be inconsistent, but over time will be consistent



Most relational DBs (Oracle, MySQL...)

Most NoSQL systems (C\*, BigTable, MongoDB,...)

NoSQL and CAP

Neo4j, Oracle, Consistency MySQL CP CA Availability AP Cassandra, DynamoDB,

MongoDB, BigTable, Redis, HBase

CouchDB